

# Inverted Fuel Reels

## Series 40 Large Frame Reels

## New Product Options

### DESCRIPTION

Reelcraft's invert reel is further testament to the endless options available within S40 large frame reel series. The series 40 invert is designed to facilitate a hanging or wall mount ideal for liquid propane, hydroseeding, or refueling applications. When combined with our newly featured Air Brake option, the S40 Invert is perfect for the fuel oil industry.

### BENEFITS

- **Lightweight** T-slot aluminum frame greatly reduces weight without sacrificing strength.
- **Proven In The Field** S40 Passed military vibration for truck transport test, a 500,000 mile equivalent.
- **Long Service Life** Self-lubricating and self-aligning bearings require little maintenance.
- **Weather Resistant** Powder coated flanges, anodized aluminum frame, and zinc-plated fasteners offer the greatest amount of corrosion protection and durability. Anodized aluminum flanges are available upon request.
- **Safety** Spool is completely enclosed by the reel base, making it impossible for the spool to become dislodged.

### RELATED PRODUCTS

The series 40 line is unique in that it is completely configurable. Specify your dimensions and Reelcraft will build your reel as standard in just 5-7 work days.



Area enlarged to show detail



Patent Pending

SERIES 40 / Inverted Fuel Reels

### SPECIFICATIONS

MODEL (without hose)	HOSE I.D. in / mm	HOSE O.D. in / mm	CAPACITY ft	PRESSURE psi / bar	WEIGHT lbs / kg	HEIGHT in / mm	LENGTH in / mm	WIDTH in / mm
<b>SERIES 40: MOTOR DRIVEN REELS</b>								
40-00262	1 1/4 32	1 3/4 34	100	600 42	135 62	31 787	29 737	23 584
40-00371	1 1/4 32	1 3/4 34	150	600 42	140 64	35 889	33 838	25 635
40-00372	1 1/4 32	1 3/4 34	200	600 42	145 66	39 991	37 940	25 635

NOTE: Base models above are configured with 12 Volt DC XP motor, chain drive, & powder coated steel flanges/side frames.

To order your reel, select desired base model and specify any additional items (if necessary) from the list below. Call us, we'll configure your reel and ship it in 5-7 working days.

MOTOR / DRIVE TYPE OPTIONS
24VDC XP Motor
115VAC XP Motor
Hydraulic Motor
6AM Air Motor
Gear Drive Option

ADDITIONAL ACCESSORIES OPTION
Aluminum Flanges/Sides
Explosion Proof Switch
Starting Solenoid
40 Amp Circuit Breaker
Junction Box EXP

AIR BRAKE OPTIONS	
MODEL	DESCRIPTION
602041	Air brake caliper & friction disc assembly
602040	Air brake caliper assembly
602039	Air brake friction disc assembly

### SPECIFICATIONS

- ✓ Max pressure 600 psi.
- ✓ Max temp 174°F (79° C). Minimum temp -60°F (-51° C).
- ✓ Available in 1", 1 1/4", and 1 1/2" hose I.D. and lengths up to 350'

### SPECIFICATIONS (AIR BRAKE)

- ✓ Extruded aluminum construction
- ✓ 2 in<sup>2</sup> frictional pad area
- ✓ Frictional disc 6 1/16" diameter
- ✓ Replaceable friction disc and caliper assembly

USA: 800-444-3134

Canada: 800-268-1756  
Europe: + 44 (0) 1536 406999  
Asia: 63-45-599-3721

**Reelcraft Industries, Inc.**

One Reelcraft Center / P.O. Box 248  
Columbia City, IN 46725  
FAX: 260-248-2605

[www.reelcraft.com](http://www.reelcraft.com)

Reelcraft Industries is  
**ISO 9001:2000**  
Certified Since 1996

